

**SPECIFICATIONS**


<b>PRIMARY GRID BARS:</b> 1 1/2" X 1 1/2" (ON CENTER)	<b>STD. PANEL THICKNESS:</b> 1"
<b>APERTURE:</b> 1 1/4"	<b>PANEL SIZE:</b> 4' X 8'
<b>LOAD BAR THICKNESS:</b> 1/4"	<b>WEIGHT:</b> 2.5 LB/SQ.FT.
<b>OPEN SPACE:</b> 68%	<b>COLOR (STD.):</b> DARK GREY (OTHER COLORS ON REQUEST)

**APPLICATION NOTES:**

1. PERIMETER CONTAINMENT IS RECOMMENDED TO PREVENT LATERAL SHIFTING.
2. CUT PEDESTAL BASE ON SCORE LINE TO POSITION PEDESTAL CLOSE TO PERIMETER.
3. MAXIMUM PEDESTAL SUPPORT SPACING ALONG GRATE PERIMETER AND UNDER BODY OF GRATE IS 24" ON CENTER.
4. ONLY KEEP PEDESTAL HEAD SPACER TABS THAT ARE NECESSARY FOR HOLDING GRATES IN POSITION.
5. GRATE SURFACE HAS AN APPLIED ANIT-SLIP COATING.

**GENERAL NOTES:**

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH ARCHATRAK SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY AND SHOULD NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY ARCHATRAK TO BE CONSIDERED ACCURATE.



**FRP GRATING**

1 1/4" X 1 1/4" MACROMESH GRATING