


INSTALLATION NOTES:

1. PERIMETER CONTAINMENT IS RECOMMENDED TO PREVENT LATERAL SHIFTING.
2. CUT PEDESTAL BASE ON SCORE LINE TO POSITION PEDESTAL CLOSE TO PERIMETER.
3. MAXIMUM PEDESTAL SUPPORT SPACING ALONG GRATE PERIMETER AND UNDER BODY OF GRATE IS 24" ON CENTER.
4. LAY 3/4" THICK JOIST ACROSS PEDESTAL HEADS AND SECURE WITH #8 1" STAINLESS STEEL MACHINE SCREWS.
5. SECURE SYNTHETIC TURF TO FRP FIBER-GRATING WITH #8 1 1/2" STAINLESS STEEL MACHINE SCREWS SCREWED THROUGH TURF SURFACE, PASSING THROUGH MESH OPENING INTO JOIST.

GENERAL NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH ARCHATRAK SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY AND SHOULD NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY ARCHATRAK TO BE CONSIDERED ACCURATE.



FRP GRATING: SYNTHETIC TURF SUPPORT

FRP GRATING SUPPORT FOR ROOFTOP INSTALLATION OF SYNTHETIC TURF