



ARCHASOL

ARCHASOL
1288 N 14TH AVE. UNIT 105
BOZEMAN, MT 59715
PHONE: (406) 551-7955
www.archasol.com

SELECT DESIRED LED COLOR:

- 3000 K
- 4000 K

SELECT DESIRED LIGHT DISTRIBUTION:

- ASYMMETRICAL
- SYMMETRICAL

SELECT DESIRED FINISH:


- ANODISED - CLEAR
- ANODISED - EBONY
- POWDER COATED - BLACK SATIN
- POWDER COATED - OTHER COLORS AVAILABLE (MIN. 15 PCS)

SELECT DESIRED MOUNT TYPE:

- BASE PLATE
- DIRECT BURY
- WALL MOUNT

SELECT DESIRED OVERALL HEIGHT:

- 11 3/8" 11 7/8" 39 3/8" 59"
- 79" 94 1/2" 98 3/8" 118"



DIRECT BURIAL MOUNTED FRONT VIEW

BASE - PLATE MOUNTED FRONT VIEW

BASE - PLATE MOUNTED FRONT VIEW

TECHNICAL SPECIFICATIONS:

SOLAR MODULE: 5 W MONOCRYSTALLINE, 5 V, 1 AMP

BATTERY: 3.2 V, 17 Ah CYLINDRICAL LIFEPO4; 3700 MIN. CYCLES (EXPECTED); DESIGN LIFE: 10+ YEARS (EXPECTED)

OPERATIONAL TIME: DUSK UNTIL DAWN FULL POWER

LED & ELECTRONICS: 8 X 5 MM PIRANHA LED SUPER BRIGHT; 3.2V; POWER: 40 MA - 280 MA (SET FOR SPECIFIED LOCATION/CONDITIONS)

OPERATING TEMPERATURE: -30°C ~ +60°C AMBIENT

CERTIFICATIONS: IP68, IK10

MATERIALS: POLES - 6106 T6 ALUMINUM MARINE GRADE; DOME - SABIC SLX LEXAN; HOUSING - SABIC LEXAN 203R; INTERNAL - STAREX ASA


WARRANTY: 10 YEARS

MANUFACTURERS NOTES:

1. CONTACT MANUFACTURER TO SELECT CORRECT POWER MODEL FOR THE SPECIFIC SITE LOCATION AND CONDITIONS

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5501-021.



SBL SOLAR BOLLARDS LIGHTS

SBL SERIES SR BOLLARD LIGHT - WITH REFLECTOR