

Section 1

Product & Company Identification

Product	Fiber Reinforced Plastic Product
Company	Archatrak Inc. 1288 N 14th Ave. Unit 105 Bozeman MT 59715
Website	www.archatrak.com
Hours	8.30am-5.30pm Mon-Fri MST
Recommended Use	+1 866 206 8316 Structural Component

Section 2

Hazard (s) Identification

Classification	In accordance with 29 C.F.R. & 1910.1200, this product is an "article" and therefore not subject to the HCS 2012 SDS and labeling requirements. The information presented is for potential end use grinding, sanding, cutting, or other mechanical work of this product.
Signal Word	Warning
Pictogram	None
Hazard Statement	May form combustible dust concentrations in air.
Precautionary Statements	None
Hazards Not Otherwise Classified	The grinding, drilling, sanding, cutting, or other mechanical working of this product may generate dusts that could act as a mechanical irritant to skin, eyes, and upper respiratory system. Vapors or products of thermal degradation generated by cutting or grinding may aggravate or cause respiratory conditions.

Section 3

Composition / Information on Ingredients

CHEMICAL COMPONENT	CAS NUMBER	PERCENT
Polymerized Resin	None	30%-75%
Fiberglass	65997-17-3	25%-70%
Quartz Silica Sand (<i>Present Within Anti-Slip Gritted Products Only</i>)	14808-60-7	1%

Section 4

First Aid Measures

Routes of Entry	Inhalation, skin, and ingestion
Signs & Symptoms of Exposure	Temporary irritation and itching to skin or eyes. Scratchiness or burning of the nose and/or throat if exposed to large amount of airborne dust from cutting or machining.
Emergency & First Aid Procedures	Wash skin well without rubbing. For eyes, use a sterile solution and flood the eye area. Change clothing after exposure. Apply antiseptic to any abraded skin area.

Section 5

Extinguishing Media:

Fire Fighting Measures

Water; Foam/Type A, B, or C Extinguishers

Special Firefighting Procedures:

Use Self-Contained Breathing Apparatus (SCBA) with full face mask operated in pressure mode.

Unusual Fire & Explosion Hazards:

Burning FRP creates a complex mixture of solid, liquid, particulate, and gases. Carbon monoxide and other organic compounds may be given off. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Section 6

Personal precautions, protective equipment, and emergency procedures:

Accidental Release Measures

Non-sparking tools should be used. Avoid dispersal of dust in the air (i.e. clearing dust surfaces with compressed air).

Methods and materials for containment and cleaning up:

Dust deposits from fabrication should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Section 7

Handling

Handling and Storage

Use personal protection equipment to minimize skin, respiratory and eye exposure to dust and fumes when cutting or grinding product. Do not rub or scratch skin if dust particles have accumulated on exposed skin. Wash all exposed skin areas thoroughly after cutting or grinding. Launder clothing separately and frequently to prevent skin exposure.

Fabrication of Product

Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Storage

No special storage conditions exist.

Section 8

Occupational Exposure Limits

- OSHA PEL
- ACGIH TLV

Exposure Controls / Personal Protection

Value

15mg/m³ (Nuisance Dust) Total
10mg/m³ (Nuisance Dust) Total

Respiratory Protection

A NIOSH-MSMA approved dust mask for dusts and mists with PEL not less than 0.1 mg/M³ when cutting or grinding.

Protective Gloves

Wear cloth gloves when handling product to prevent cuts, scratches, or abrasions.

Eye Protection

Wear protective eyewear with side shield or ventilated goggles when cutting or grinding product.

Other Protective Equipment

Barrier cream and long sleeve shirts with closed collars, long pants or protective clothing.

Ventilation

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents, an explosion suppression system, or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Use only appropriately classified electrical equipment and powered industrial trucks.

Section 9**Physical and Chemical Properties****PROPERTY:****MEASUREMENT:**

Appearance:

- Physical State
- Color

Solid Article
Various Colors

Odor

Low to none

Odor Threshold

N/A

pH

N/A

Melting Point/Freezing Point

N/A

Initial Boiling Point

N/A

Flash Point

N/A

Evaporation Rate

N/A

Flammability

N/A

Upper/Lower Flammability Limits

N/A

Vapor Pressure

N/A

Vapor Density

N/A

Relative Density

1.5-2.0

Solubility

Not applicable

Partition Coefficient:

- n-octanol/water

Not applicable

Auto-Ignition Temperature

Not applicable

Decomposition Temperature

Not applicable

Viscosity

Not applicable

Section 10**Stability and Reactivity Data**

Stability

Solid Article

Conditions to Avoid

Sources of ignition, sparks, or flames, extremely high temperatures

Incompatibility

Strong oxidizing acid

Hazardous Decomposition or Byproducts

Not applicable

Hazardous Polymerization

Will not occur

Section 11**Toxicological Information**

Routes of Exposure:

- Inhalation
- Eye
- Skin
- Ingestion

Nuisance dust from machining can cause irritation.
Nuisance dust from machining can cause irritation.
Nuisance dust from machining can cause irritation.

N/A

Delayed and Immediate Effects

N/A

Acute Toxicity

N/A

Carcinogenicity Status

- National Toxicology Program (NTP)
- International Agency for Research on Cancer (IARC)
- OSHA

N/A

N/A

N/A

Section 12

Eco toxicity
Persistence and Degradability
Bio Accumulative Potential
Mobility in Soil

Ecological Information

No data
No data
No data
No data

Section 13

Waste Disposal Method

Disposal Considerations

Control and collect any dust generated in sturdy containers to prevent dispersal.
Dispose of in accordance with all federal, state, and local regulations.
Generally, the dust is not considered a hazardous waste.

Section 14

Shipping Name
Shipping Symbols
Hazard Class
ID No
Packing Group
Label
Special Provisions

Transport Information

Not regulated
N/A
Not hazardous
N/A
Not determined
Not required
None

Section 15

Environmental Regulations

- RCRA
- CERCLA
- SARA 311/312 Codes
- SARA 313

Regulatory Information

Not listed
Not listed
None
None above de minimis quantity

Section 16

Refer to NFPA 654

HMIS

Issue Date

Other Information

Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Health = 0
Fire = 1
Reactivity = 0

3rd April 2024

We believe that the above information is valid and reliable. The information, however, is provided without any representation of warranty, expressed or implied, regarding the accuracy of correctness. The conditions of methods of handling, storage, use, cutting, grinding, disposal, or other use of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use, cutting, grinding, disposal, or any other use of this product.

© 2025 Archatrak Inc., All Rights Reserved