


SECTION VIEW

ATTACH SYNTHETIC TURF TO ARCHATRAK FRP MICROMESH GRATING, ELEVATED AND LEVELED ON SLOPING SURFACES USING ADJUSTABLE HEIGHT PEDESTALS TO CREATE LAWN AREAS ON BALCONIES, ROOFTOP DECKS AND TERRACES.

NOTES:

1. PERIMETER CONTAINMENT IS RECOMMENDED TO PREVENT LATERAL SHIFTING.
2. CUT PEDESTAL BASE ON SCORE LINE TO POSITION PEDESTAL CLOSE TO PERIMETER.
3. PLACE PEDESTAL EVERY 24" ALONG GRATING PERIMETER AND UNDER BODY OF GRATING ON 24" CENTER.
4. SECURE TURF TO TOP OF GRATING PER TURF MANUFACTURER'S INSTRUCTIONS. A NON SLIP GEOTEXTILE MAT BETWEEN THE TURF AND THE FRP PANELS MAY BE RECOMMENDED.
5. ADD INFILL AS INSTRUCTED BY TURF MANUFACTURER.
6. FOR FRP GRATING PRODUCT INFORMATION VISIT [HTTPS://WWW.ARCHATRAK.COM/FIBERGLASS-GRATING/](https://www.archatrak.com/fiberglass-grating/)
7. DO NOT SCALE DRAWING.



ELEVATED SYNTHETIC TURF

INSTALLATION OVER FRP GRATING AND HEIGHT-ADJUSTABLE PEDESTALS