

■ Archatrak MSDS | Ipe Wood Deck Tiles

Section 1

Product

Company

Website

Hours 8.30am-5.30pm Mon-Fri MST

Recommended Use

Product & Company Identification

Ipe Wood Deck Tiles

Archatrak

1001 W Oak St. Unit 101

Bozeman MT 59715

www.archatrak.com

+1 866 206 8316

Deck material for elevated decks

Section 2

Classification

Signal Word

Pictogram

Hazard Statement

Precautionary Statements

Hazards Not Otherwise Classified

Hazard (s) Identification

In accordance with 29 C.F.R. & 1910.1200, this product is an "article" and therefore not subject to the HCS 2012 SDS and labeling requirements. The information presented is for potential end use grinding, sanding, cutting, or other mechanical work of this product.

Warning

None

May form combustible dust concentrations in air when cut or machined

None

The grinding, drilling, sanding, cutting, or other mechanical working of this product may generate dusts that could act as a mechanical irritant to skin, eyes, and upper respiratory system. Ipe wood dust contains silica which is hazardous and may elicit allergic contact dermatitis in sensitized individuals.

Section 3

Composition / Information on Ingredients

CHEMICAL COMPONENT	CAS NUMBER	PERCENT
Ipe wood / wood dust	N/A	N/A

Section 4

Routes of Entry

Signs & Symptoms of Exposure

Emergency & First Aid Procedures

First Aid Measures

Inhalation and ingestion of dust in cutting or sanding

Temporary irritation and itching to skin or eyes if exposed to large amount of airborne dust from cutting or machining

Wash skin well without rubbing. For eyes, use a sterile solution and flood the eye area.

Section 5

Extinguishing Media:

Special Firefighting Procedures:

Unusual Fire & Explosion Hazards:

Fire Fighting Measures

Water, CO2, Sand

Use water to wet down wood dust to reduce the likelihood of ignition and dispersion of dust into the air.

Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source, is a potential dust explosion hazard.

Section 6

Personal precautions, protective equipment, and emergency procedures:

Methods and materials for containment and cleaning up:

Accidental Release Measures

Avoid dispersal of dust in the air (i.e. clearing dust surfaces with compressed air).

Dust deposits from fabrication should not be allowed to accumulate atmosphere in sufficient concentration.

Section 7

Handling

Wood products are prone to have splinters and other potentially sharp features. Use caution when handling. Always wear puncture resistant work gloves.

Fabrication of Product

Minimize dust generation and accumulation. Wear an approved particulate respirator and tight fitting goggles when cutting, machining or sanding and ensure adequate ventilation is maintained when working in a confined area.

Storage

No special storage conditions exist.

Section 8

Respiratory Protection

Wear a NIOSH-MSMA approved dust mask for protection against airborne particulates when cutting or machining

Protective Gloves

Wear puncture resistant work gloves when handling product to prevent cuts, scratches, or abrasions.

Eye Protection

Wear protective eyewear with side shield or ventilated goggles when cutting, machining or sanding product.

Other Protective Equipment

Long sleeve shirts with closed collars and long pants are advised.

Ventilation

When cutting, sanding or machining tiles, make sure that airborne particulates are allowed to ventilate.

Section 9**Physical and Chemical Properties****PROPERTY:****MEASUREMENT:**

Appearance:

▪ Physical State

Solid Article

Odor

Low to none

Odor Threshold

N/A

pH

N/A

Melting Point/Freezing Point

N/A

Initial Boiling Point

N/A

Flash Point

N/A

Evaporation Rate

N/A

Flammability

N/A

Upper/Lower Flammability Limits

N/A

Vapor Pressure

N/A

Vapor Density

N/A

Relative Density

1.5-2.0

Solubility

Not applicable

Partition Coefficient:

▪ n-octanol/water

Not applicable

Auto-Ignition Temperature

Combustible when exposed to open flames or heat sources in excess of 350°F (177°C)

Decomposition Temperature

Not applicable

Viscosity

Not applicable

Section 10**Stability**

Stable

Conditions to Avoid

Sources of ignition, sparks, or flames, extremely high temperatures

Incompatibility

N/A

Hazardous Decomposition or Byproducts

Burning can produce irritating & toxic fumes & gases, including CO, aldehydes and inorganic acids

Hazardous PolymerizationWill not occur

Stability and Reactivity Data

Section 11**Routes of Exposure:**

- **Inhalation**

Dust from machining contains silica, posing a respiratory hazard causing silicosis and other lung diseases.

- **Eye**

Nuisance dust from machining can cause irritation.

- **Skin**

Nuisance dust from machining can cause irritation.

- **Injection**

N/A

Delayed and Immediate Effects

N/A

Acute Toxicity

N/A

Carcinogenicity Status

- **National Toxicology Program (NTP)**

N/A

- **International Agency for Research on Cancer (IARC)**

N/A

- **OSHA**

N/A

Toxicological Information

Section 12**Eco toxicity**

No data

Persistence and Degradability

Wood wastes would be expected to be naturally biodegradable.

Bio Accumulative Potential

No data

Mobility in SoilNo data

Ecological Information

Section 13**Waste Disposal Method**

Control and collect any dust generated in sturdy containers to prevent dispersal.

Dispose of in accordance with all federal, state, and local regulations. Generally, the dust is not considered a hazardous waste.

Disposal Considerations

Section 14**Shipping Name**

Not regulated

Shipping Symbols

N/A

Hazard Class

Not hazardous

ID No

N/A

Packing Group

Not determined

Label

Not required

Special ProvisionsNone

Transport Information

Section 15

Regulatory Information

Environmental Regulations

- RCRA
- CERCLA
- SARA 311/312 Codes

No information available.

Wood Dust is not listed as a CERCLA hazardous substance

Lpe wood is considered under applicable definitions of "Hazard Categories" under SARA Title III Sections 311 and 312 to meet the following categories:

- Immediate (acute) health hazard - Yes (dust)
- Delayed (chronic) health hazard - Yes (dust)
- Fire hazard - No
- Reactivity hazard - No
- Sudden release hazard - No

- SARA 313

This product does not contain any chemical ingredients that exceed the threshold reporting levels established by SARA Title III, section 313 and 40 CFR section 372

Section 16

Other Information

Refer to NFPA 654

Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Issue Date

3rd April 2024

We believe that the above information is valid and reliable. The information, however, is provided without any representation of warranty, expressed or implied, regarding the accuracy of correctness. The conditions of methods of handling, storage, use, cutting, grinding, disposal, or other use of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use, cutting, grinding, disposal, or any other use of this product.

© 2024 Archatrak All Rights Reserved