




T20 PORCELAIN PAVER -
FIXED TO THE PEDESTAL
HEAD WITH A STAINLESS
STEEL SCREW AND WASHER



PLAN VIEW




PLAN VIEW
ARCHATRAK STEEL TRAY



INSTALLATION

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 4879-109.



T20 PORCELAIN PAVERS: 3/4" THICK

T20 PORCELAIN PAVERS: LOCK DOWN SYSTEM FOR WIND UPLIFT, WITH TRAY