



T30 PORCELAIN PAVER



PLAN VIEW

THE PAVERS ARE SECURELY FIXED TO THE PEDESTAL HEAD WITH A STAINLESS STEEL SCREW INSERTED THROUGH THE CENTER OF THE WASHER WHICH IN TURN SCREWS INTO THE TAPPED HEAD OF THE PEDESTAL

STEEL HOLD-DOWN WASHER




KERF

ARCHATRAK PEDESTAL

INSTALLATION

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 4879-099.



T30 PORCELAIN PAVERS: 1 1/8" THICK

PORCELAIN PAVER LOCK DOWN SYSTEM FOR WIND UPLIFT