




USE ARCHATRAK FRP GRATING ELEVATED AND LEVELED ON SLOPED SURFACES USING ADJUSTABLE HEIGHT PEDESTALS FOR BOARDWALKS, ROOFTOP DECK PAVING AND GREEN ROOF ACCESS WALKWAYS.

SPECIFICATIONS

PRIMARY GRID BARS: 1 1/2" X 1 1/2" (ON CENTER)

SECONDARY GRID BARS: 3/4" X 3/4" (ON CENTER)

APERTURE: 1/2" X 1/2"

LOAD BAR THICKNESS: 1/4" (PRIMARY) 1/4" (SECONDARY)


OPEN SPACE: 42%

MANUFACTURER NOTES:

1. PERIMETER CONTAINMENT IS RECOMMENDED TO PREVENT LATERAL SHIFTING.
2. CUT PEDESTAL BASE ON SCORE LINE TO POSITION PEDESTAL CLOSE TO PERIMETER.
3. MAXIMUM PEDESTAL SUPPORT SPACING ALONG GRATE PERIMETER AND UNDER BODY OF GRATE IS 24" ON CENTER.
4. ONLY KEEP PEDESTAL HEAD SPACER TABS THAT ARE NECESSARY FOR HOLDING GRATES IN POSITION.
5. GRATE SURFACE CONTAINS AN ANTI-SLIP COATING.
6. FOR PRODUCT INFORMATION VISIT <https://www.archatrak.com/fiberglass-grating/>

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 4879-090.



FRP GRATING

1/2" X 1/2" MIDIMESH GRATING